



Saves Your Energy

PRODUCT CARD

2016-08-29

SO28

Tempiamasis gnybtas

Tipas	SO28
GTIN	6418677404580
Pavadinimas	Tempiamasis gnybtas AAAC 25-50 mm ² neizoliuotam nešančiajam laidininkui
Aprašymas	Skirtas žemos įtampos oro kabeliams su neizoliuotu nešančiuoju laidininku (AMKA). Nešantįjį laidininką galima įstatyti į gnybto grovelį, atsukus varžtus, todėl nebūtina jo nukirpti. SMFL įvairiems nešančiojo laidininko skerspjūviams: - 25 mm ² - 6,6 kN, - 35 mm ² - 9,3 kN, - 50 mm ² - 13,2 kN.



Techninė specifikacija

Matmenys

Svoris:	0.25 kg
Nešančiojo laidininko skersmuo:	5.8 ... 8 mm
Nešantysis laidininkas:	25 ... 50 mm ²

Mechaninis

SMFL:	13.2 kN
Užveržimo momentas:	20 Nm

Ratings

ETIM:

Specification

Use:	Used for the dead-ending of AAAC conductors (e.g.AMKA cable messenger) by means of hooks to either a pole or a wall.
------	--

Construction:

Construction:

Component	Material
Body	Corrosion resistant aluminium alloy
U-Bolts	Hot-dip galvanised steel

Installation:

The messenger is fitted directly in to groove without cutting. Tightening torque of bolts 20 Nm

Tools required:

Articulated spanner ST 20

Markings:

SO 28

Standard:

EN 50483-2

Pakuotė

Pakuotė

Size:	50
Length:	385 mm
Width:	260 mm
Height:	165 mm
Weight (net):	11.58 kg
Weight (brt):	12.5981 kg
Volume:	0.0165

Pallet package

Size:	2700
Length:	1200 mm
Width:	800 mm
Height:	1140 mm
Weight (net):	625.32 kg
Weight (brt):	646 kg
Volume:	1.0944