

ENSTO

SDI37

Smaiginis izoliatorius

Tipas	SDI37
GTIN	6418677408731
Pavadinimas	Smaiginis izoliatorius 24 kV, su tempimo įvore
Aprašymas	SDI37 naudojamas neizoliuotiems arba izoliuotiems laidininkams. Tinka montuoti ant smaigo SOT24 (SFS 4385). Viršutiniame izoliatoriaus griovelyje esanti plastikinė įvorė, leidžia tempti laidininką, nenaudojant montažinių skriemulių. Laidas rišamas prie izoliatoriaus viršutinio griovelio arba kaklelio, linijoje kampu tik prie kaklelio. Srovės nuotėkio kelias 325 mm, kaklelio skersmuo 85 mm.



Techninė specifikacija

Matmenys

Svoris:	3.8 kg
Izoliatoriaus kaklelis:	85 mm
Srovės nuotėkio atstumas:	325 mm

Elektrinės vertės

Didžiausia sistemos įtampa:	24 kV
Impulsinės išlydžio įtampos atlaikymas sausoje aplinkoje:	≥ 125 kV
Impulsinės išlydžio įtampos atlaikymas šlapioje aplinkoje:	≥ 50 kV

Savybės

Smaiginis izoliatorius:	SOT24
-------------------------	-------

Mechaninis

Suardanti apkrova:	12.5 kN
--------------------	---------

Ratings

ETIM 7: EC003514 High voltage insulator

Specification

Use:	Used with bare wires or covered conductors.
Construction:	SDI37 has an incorporated plastic thimble in the top, which enables the conductors to be pulled directly in the insulator groove without other pulleys.
Installation:	A pulling rope is first passed through the plastic sleeves and the conductor is then pulled in the normal manner. If necessary the sleeve can be rotated so that the rope/conductor cannot come out of the groove. When the conductor has been tightened it is tied to either the top groove or the side neck of the insulator as appropriate. The plastic pulling sleeve can be left in place.
Markings:	SDI37
Standard:	SFS 5004, IEC 383

ETIM 10

ETIM

Material:	Porcelain
Breaking load:	12.5 kN
Length:	212 mm
Wet power frequency withstand voltage:	50 kV
Min. dry lightning impulse withstand voltage:	125 kV
Rated voltage:	24 kV
Model:	Pin insulator
Creepage path:	325 mm
Diameter:	170 mm
Weight:	3.8 kg

Pakuotė

Pakuotė

Unit:	PCS
Size:	3
Length:	520 mm
Width:	180 mm
Height:	180 mm
Weight (net):	11.4 kg
Volume:	0.0168

Pallet package

Unit:	PCS
Size:	90
Length:	1200 mm

Width:	800 mm
Height:	1030 mm
Weight (net):	342 kg
Weight (brt):	362 kg
Volume:	0.9888

